

# PLASTOFUSED 2.0 ECO VERSION



## Description

Our new quick and easy solution for plastic-repair.

Our new PLASTOFUSED 2.0 is equipped with a LCD-display which shows the set temperature and the real temperature. We can reach higher temperatures by using a lower air volume as this is the key to be able to achieve a good bonding. With this we get the plastic faster up to its own melting flow index (MFI) which then makes it ideal for bonding. With the special designed flat welding strip we created a tool for a quick, simple and high quality plastic-repair.

## Benefits

- Quick & efficiently
- Ideal mixture of air pressure and temperature
- Easy to handle
- High-quality main-housing
- Modern design
- Wide range of accessories
- Different Melting-Strips
- Different fields of application



## Scope of delivery

- PLASTOFUSED 2.0 unit
- Hose package 2m incl. handle
- Hot air nozzle
- Melting-Strips (PU 15 pcs.), black for Polypropylen (PP-EPDM)
- Melting-Strips (PU 15 pcs.), black for Acrylnitril-Butadien-Styrol (ABS)
- Robust cardboard packaging incl. inlay
- Manual

# Technical data

Operating voltage	230 V~ / 50 Hz
Power	320 W / 1,49 A
Adjustable temperature	160...480 °C / 320...896 °F
Display	double-spaced LCD-display
Nozzle ø	5 mm
Lenght of hose	1000 mm
Made in	Germany

# Dimensions & Weight

L x W x H	cm x cm x cm
Weight	kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH  
Im Oberen Tal 31  
74858 Aglasterhausen  
GERMANY

Tel: +49 (0) 6262 / 92 605-0  
Fax: +49 (0) 6262 / 92 605-29  
Mail: [info@kamatec.com](mailto:info@kamatec.com)  
Web: [www.kamatec.com](http://www.kamatec.com)