

BLASTING LANCE



Description

The GP 5-8 Granule Jet Blasting Device is designed for removing carbonized material from the inlet channel and the inlet valves in combustion engines. The device is approved for models by BMW and MINI. A big advantage is the operation with walnut shell granule. It is organic and does not damage the motor compartment. After cleaning, the granule gets exhausted without any residues. The inlet channel and the inlet valves were cleaned — without any chemical auxiliaries. Due to the safety valve the maximal pressure can not exceeded. We recommend to wear protective clothes.

This Blasting Lance is suitable for following types of motor: N14

Benefits

- Quick and effective removal of carbonized material.
- No use of chemical auxiliaries.
- Simple use and sustainable results.

Scope of delivery

- Blasting Lance

Technical data

| Purpose (Motor type) | Wert |
|-------------------------|---------------|
| Tube diameter (inner) | Ø 6 mm |
| Tube diameter (outside) | Ø 8 mm |
| Width across flats | 17 mm |
| Recommended granule | 0,45 - 0,8 mm |
| Manufacturer | TKR |

Dimensions & Weight

| | |
|-----------|--------------|
| L x W x H | cm x cm x cm |
| Weight | kg |

For further questions please do not hesitate to contact us.

KAMATEC GmbH
Im Oberen Tal 31
74858 Aglasterhausen
GERMANY

Tel: +49 (0) 6262 / 92 605-0
Fax: +49 (0) 6262 / 92 605-29
Mail: info@kamatec.com
Web: www.kamatec.com