

GLUEPULLER GP2 SYSTEM



Description

The gluing repair technique is standard procedure for most modern PDR technicians. It is very practical for areas that cannot be reached with conventional PDR tools. How it works: Glue an appropriate knob to the damaged area using our hot melt glue and gun included in the kit. Once the glue has cooled, attach the Glue Puller GP2 to the knob. Gently squeeze the handle and watch the dent come out.

Benefits

- Eliminates the need to dismantle body panels in many cases
- Dents are always accessible
- Saves time and money
- Easy handling

Scope of delivery

- Glue Gun 220V / EU
- Pull Knob Small Round
- Pull Knob Small Flat
- Pull Knob Big Round
- Pull Knob Big Flat
- Pull Knob GT-15
- Pull Knob GT-25
- Pull Knob HT-15
- Pull Knob HT-20
- Knock Down
- Pulling Unit
- 250g summer use Beige Glue
- 250g winter use Blue Glue

Technical data

Bezeichnung:	Wert
--------------	------

Dimensions & Weight

L x W x H	42,00 cm x 30,00 cm x 11,00 cm
Weight	3,2 kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH
Im Oberen Tal 31
74858 Aglasterhausen
GERMANY

Tel: +49 (0) 6262 / 92 605-0
Fax: +49 (0) 6262 / 92 605-29
Mail: info@kamatec.com
Web: www.kamatec.com