

PLASTOFUSED 2.0 MOBILE BASIC VERSION



Description

Our new PLASTOFUSED-System is equipped with a LCD-display which shows the set temperature and the real temperature. We can reach higher temperatures by using a lower air volume as this is the key to be able to achieve a good bonding. With this we get the plastic faster up to its own melting flow index (MFI) which then makes it ideal for bonding. With the special designed flat welding strip we created a tool for a quick, simple and high quality plastic-repair.

Benefits

- Schnell & wirtschaftlich
- Für ABS und PP-EPDM geeignet
- Einfache Bedienung, dank flexiblem Schlauchpaket
- Ideales Gemisch aus Temperatur und Luftstrom
- Hochwertiges Gehäuse & modernes Design im Zusammenspiel mit Benutzerfreundlichkeit
- Mobil durch speziell angepassten Fahrwagen

Scope of delivery

- PLASTOFUSED 2.0 unit
- Hose package 2m incl. handle
- Hot air nozzle
- PLASTOFUSED-Trolley
- Special flat-nose-plier
- Plastic Scraper, 3-edged
- Pneumatic grinder incl. 2 grinding discs C.40
- Melting-Strips (PU 15 pcs.), black for Polypropylen (PP-EPDM)
- Melting-Strips (PU 15 pcs.), black for Acrylnitril-Butadien-Styrol (ABS)
- Robust cardboard packaging incl. inlay
- Manual

Technical data

Operating voltage	230 V~
Power	320 W / 1,49 A
Adjustable temperature	160...480 °C / 320...896 °F
Display	double-spaced LCD-display
Nozzle ø	5 mm
Hose package	2000 mm / removable
Protection class	IP 42
Manufacturer	KAMATEC
Made in	Germany

Dimensions & Weight

L x W x H	140 cm x 248 cm x 169 cm
Weight	kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH
Im Oberen Tal 31
74858 Aglasterhausen
GERMANY

Tel: +49 (0) 6262 / 92 605-0
Fax: +49 (0) 6262 / 92 605-29
Mail: info@kamatec.com
Web: www.kamatec.com