

# ADAPTER 60 KN



□

## Description

Screw the receiving socket in the hydraulic cylinder up to the contact surface and hand-tighten with the wrench set. Do not use force. Then screw the adapter into the rivet clamp receiving socket up to the contact surface and hand-tighten. All riveting tools must only be fitted/removed with compressed air connected. Then screw in the riveting tool punch required for the process into the receiving socket and hand-tighten with the supplied wrench set.

Screw the corresponding counter-piece of the punch into the adapter in the rivet clamp receiving socket and hand-tighten with the supplied wrench set. Do not use force! If necessary, the riveting tools between the hydraulic cylinder and the rivet clamp can be switched.

## Benefits

- Use of existing riveting tools (UN 2.0)
- the HA XT2 is threaded accordingly

## Scope of delivery

- Adapter
- Receiving socket

## Technical data

Regulated to	60 kN / 6 T
Thread	M8 > M6
Made in	Germany
Manufacturer	TKR PowerTools

## Dimensions & Weight

L x W x H	cm x cm x cm
Weight	kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH  
Im Oberen Tal 31  
74858 Aglasterhausen  
GERMANY

Tel: +49 (0) 6262 / 92 605-0  
Fax: +49 (0) 6262 / 92 605-29  
Mail: [info@kamatec.com](mailto:info@kamatec.com)  
Web: [www.kamatec.com](http://www.kamatec.com)